

DOUBLE WRAPPER FOR COILS 630 ÷ 1250MM



READY
TO START



DOUBLE WRAPPER FOR COILS 630 ÷ 1250MM

SIMPLE AND PERFORMING: Designed and built to adapt to any production line where the winding must be extremely versatile. Two different versions: "Economy" → with coils unloading through your pallet truck; "Smart" → with autonomous coil discharge realized by hydraulic and electromechanical movement device. On request, it is equipped with a completely automatic COIL CHANGE system

POLYVALENT: Possibility to wrap the product on rolls of different sizes including three diameters Ø 600 and Ø 1250 mm

SAFETY CONTROLLER: Equipped with safety sensors control panel - Alarms with open door shutdown - Slow down for reel change. LCD display to display speed and meter-size.

IN COMPLIANCE WITH THE REGULATIONS: The winders manufactured by us are equipped with all the safety devices in compliance with the machinery directives 2006/42 C€

TECHNICAL DATA

Reel Minimum dimensions	630 x 405 mm with hole Ø 40 mm
Reel Max dimensions	1250 x 735 mm with hole Ø 80 mm
Production speed	max 250 mt/min with coils Ø 630 mm
Production speed	max 400 mt/min with coils Ø 1250 mm
D.C – AC engine	6,3 Kw.
Active protections	Stop sensor- Transparent panels in PET – G Qualified with breaking tes
Overall dimensions:	2900 / 1800 / 1900 mm L/P/H